CLAIMS

1.   A control system for controlling external systems coupled to a local area network, the control system comprising:

a control unit coupled to the local area network, the control unit comprising system control software operative to forward a tagged external system message that includes a control command to at least one external system and to receive a tagged external system message that includes status information back from the at least one external system upon query from the control unit; and

a first subscriber station in communication with the control unit, the first subscriber station operative to interface with the control unit using tagged subscriber station messages, the tagged subscriber station messages being applicable to a subscriber interface of the first subscriber station.

2.   The system of claim 1, wherein the tagged subscriber station messages are HTML documents.

3.   The system of claim 1, wherein the tagged subscriber station messages are XML messages.

4.   The system of claim 1, wherein the tagged external system messages are XML messages.

5.   The system of claim 1, wherein the control unit further comprises:

control unit aggregation means for aggregating control data that facilitates control of at least two external systems, the control data capable of being concurrently displayed on a common screen by the subscriber interface of the first subscriber station.

38

6. The system of claim 5, wherein the control unit further comprises:

means for identifying a subscriber device associated with the first subscriber station;

means for identifying external systems that are subscriber controllable systems based at least in part on the subscriber device associated with the first subscriber station;

means for providing display content to the first subscriber station, the display content including menu content for a set of the subscriber controllable systems; and

means for providing display layout control data to the first subscriber station, the display layout control data being applicable to the subscriber interface of the first subscriber station.

7. The system of claim 1, wherein the system further comprises:

a second subscriber station in communication with the control unit, the second subscriber station operative to interface with the control unit using tagged subscriber station messages, the tagged subscriber station messages being applicable to a subscriber interface of the second subscriber station.

8. The system of claim 1, wherein the control unit further comprises:

an aggregation module operative to aggregate control data that facilitates control of at least two external systems, the control data capable of being concurrently displayed on a common screen by the subscriber interface of the first subscriber station.

9. The system of claim 8, wherein the control unit further comprises:

a subscriber device identification module operative to identify a subscriber device associated with the first subscriber station;

a subscriber controllable external systems identification module coupled to the subscriber device identification module and operative to identify external systems that

are subscriber controllable systems based at least in part on the subscriber device associated with the first subscriber station;

a content module coupled to the subscriber controllable external systems identification module and operative to provide display content to the first subscriber

5   station, the display content including menu content for a set of the subscriber controllable systems; and

a layout module coupled to the subscriber device identification module and operative to provide display layout control data to the first subscriber station, the display layout control data being applicable to the subscriber interface of the first subscriber

10   station.

10.   A control unit for facilitating the control of external systems, the control unit and the external systems being coupled to a local area network, the control unit comprising:

15   system control software operative to interface with a first subscriber station using tagged subscriber station messages, the first subscriber station in communication with the control unit through a network, the tagged subscriber station messages being applicable to a subscriber interface of the first subscriber station, the system control software operative to forward a tagged external system message that includes a control command

20   to at least one external system and to receive a tagged external system message that includes status information back from the at least one external system.

11.   The control unit of claim 10, wherein the tagged subscriber station messages are HTML documents.

25

12.   The control unit of claim 10, wherein the tagged subscriber station messages are XML messages.

40

13.   The control unit of claim 10, wherein the tagged external system messages are XML messages.

14.   The control unit of claim 10, wherein the control unit further comprises:

control unit aggregation means for aggregating control data that facilitates control of at least two external systems, the control data capable of being concurrently displayed on a common screen by the subscriber interface of the first subscriber station.

15.   The control unit of claim 14, wherein the control unit further comprises:

means for identifying a subscriber device associated with the first subscriber station;

means for identifying external systems that are subscriber controllable systems based at least in part on the subscriber device associated with the first subscriber station;

means for providing display content to the first subscriber station, the display content including menu content for a set of the subscriber controllable systems; and

means for providing display layout control data to the first subscriber station, the display layout control data being applicable to the subscriber interface of the first subscriber station.

16.   The system of claim 10, wherein the control unit further comprises:

an aggregation module operative to aggregate control data that facilitates control of at least two external systems, the control data capable of being concurrently displayed on a common screen by the subscriber interface of the first subscriber station.

17.   The system of claim 16, wherein the control unit further comprises:

a subscriber device identification module operative to identify a subscriber device associated with the first subscriber station;

41

a subscriber controllable external systems identification module coupled to the subscriber device identification module and operative to identify external systems that are subscriber controllable systems based at least in part on the subscriber device associated with the first subscriber station;

5   a content module coupled to the subscriber controllable external systems identification module and operative to provide display content to the first subscriber station, the display content including menu content for a set of the subscriber controllable systems; and

a layout module coupled to the subscriber device identification module and

10   operative to provide display layout control data to the first subscriber station, the display layout control data being applicable to the subscriber interface of the first subscriber station.

18.   In a control unit coupled to a local area network, a method for controlling

15   external systems coupled to the local area network, the method comprising:

receiving a first signal from a first subscriber station;

responsive to the first signal, forwarding a tagged subscriber station message to the first subscriber station, the tagged subscriber station message being applicable to the subscriber interface of the first subscriber station;

20   receiving a second signal from the first subscriber station based at least in part on the tagged subscriber station message; and

forwarding a tagged external system message that includes a control command to at least one external system based at least in part on the second signal from the first subscriber station.

25

19.   The method of claim 18, wherein the method further comprises:

42

after forwarding a tagged external system message to the at least one external

system, receiving a tagged external system message that includes status information back

from the at least one external system.

5   20.   The method of claim 19, wherein the method further comprises:

responsive to the tagged external system message that includes status

information, forwarding a second tagged subscriber station message to the first

subscriber station, the second tagged subscriber station message including the status

information.

10

21.   The method of claim 19, wherein the tagged external system messages are

XML messages.

22.   The method of claim 18, wherein the tagged subscriber station messages

15   are HTML documents.

23.   The method of claim 18, wherein the tagged subscriber station messages

are XML messages.

20   24.   The method of claim 18, wherein receiving a first signal comprises:

based at least in part on the first signal, determining if the first subscriber station

is associated with a subscriber with control access to the at least one external system; and

if the first subscriber station is associated with a subscriber with control access,

forwarding a tagged subscriber station message to the first subscriber station, the tagged

25   subscriber station message being applicable to the subscriber interface of the first

subscriber station;

else, forwarding an access-denied signal to the first subscriber station indicating

that the first subscriber station is not associated with a subscriber with control access.

43

25. The method of claim 24, wherein determining if the first subscriber station is associated with a subscriber with control access comprises:

determining a subscriber identification associated with a subscriber using the first

5   subscriber station; and

based on the subscriber identification, determining whether the subscriber has control access.

26. The method of claim 18, wherein the method further comprises:

10   identifying a subscriber device associated with the first subscriber station;

identifying external systems that are subscriber controllable systems based at least in part on the subscriber device associated with the first subscriber station;

providing display content to the first subscriber station , the display content including menu content for a set of the subscriber controllable systems; and

15   providing display layout control data to the first subscriber station, the display layout control data being applicable to the subscriber interface of the first subscriber station.